



Mundschutz BioClean Clearview

pure¹¹-Nr.: 03429, Hersteller: BioClean



Zusammenfassung

- Neue pure11-Artikelnummer (ab 01.07.2023): 1103429
- Clearview, mit Schutzvisier
- Nasenbügel
- 3-lagig
- Latexfrei
- Das Visier ist beschlagfrei und bietet einen hohen Spritzschutz
- Gammabestrahlt

Empfohlene Reinraumklassen

ISO ☐ 3 ☐ 4 ☒ 5 ☒ 6 ☒ 7 ☒ 8 ☒ 9

GMP ☐ ☐ ☒ A/B ☐ ☒ C ☒ D ☐

Produktvarianten

pure¹¹-Nr.: 03429W

Farbe: Weiß / Herst.-Nr.: VFM210-T / VE: 100 Stück

Quelle: <https://www.pure11.de/mundschutz-bioclean-clearview-0>

BIOCLEAN CLEARVIEW™ Sterile Visor Facemask VFM

About

Providing high particle and bacterial filtration efficiency, the latex-free and low-linting BioClean VFM™ Sterile Visor Facemask ensures protection, combined with comfort and exceptional breathability. The optically clear, distortion-free anti-fog visor provides additional splash protection.

Materials

INNER FACING LAYER:

Non-woven polypropylene/polyethylene (hydrophilic)

FILTER LAYER:

Meltblown polyester

OUTER FACING LAYER:

Non-woven spunbonded polyester (hydrophobic)

FASTENINGS:

Ties: Non-woven Polypropylene

Loops: Polyurethane (with blue plastic clip fastener)

NOSE-BAND:

Plastic coated steel

SPLASH PROTECTION

OPTICALLY CLEAR ANTI-FOG VISOR

HYDROPHOBIC OUTER LAYER

HYDROPHILIC INNER LAYER

LATEX-FREE

Features

- Optically clear anti-fog & distortion free visor
- Latex-free
- High bacterial & particle filtration efficiency
- Looped or tie-on versions
- ISO Class 4 & EU GMP Grade A compatible



Mr. & Mrs Phil Trayshon™ represent BioClean's range of GMP compatible cleanroom facemasks

Quality Standards

- Manufactured in a facility holding ISO 9001:2008
- Processed in an NEBB certified ISO Class 4 cleanroom environment
- Sampling and inspection in accordance with ISO 2859-3:1993

Sterilization

Method: Gamma irradiation
Minimum Dose: 25kGy
Sterility Assurance Level: 10^{-6}

Shelf Life

Five (5) years from date of manufacture

Physical Properties

COLOUR	White
STYLE	Tie-on or looped (supplied with a blue plastic clip fastener)
LENGTH (± 5 mm)	210mm
WIDTH (± 5 mm)	95mm

Performance Information

COMPATIBILITY	ISO Class 4 & EU GMP Grade A
PARTICLE FILTRATION EFFICIENCY (PFE)@ 0.3 MICRON	>96%
BACTERIAL FILTRATION EFFICIENCY (BFE) @ 3.0 MICRON	>94%
DIFFERENTIAL PRESSURE (ΔP), mm H ₂ O/cm ²	3.2

TO ORDER

Re-order code

VFM210-L (Looped)
VFM210-T-SLOT (Tie-on/slots)

Packing

VFM210-L (Looped with blue clip fastener);
One piece per sealed inner PE bag; 25 inner bags per sealed outer PE bag; four outer bags per lined carton (100 pieces)
VFM210-T (Tie-on);
One piece per sealed inner PE bag; 25 inner bags per sealed outer PE bag; four outer bags per lined carton (100 pieces)

CONTACT

Europe

(Headquarters)

Nitritex Ltd.
Minton Enterprise Park,
Oaks Drive,
Newmarket, Suffolk,
CB8 7YY
United Kingdom
T: +44 (0) 1638 663338
F: +44 (0) 1638 668890
E: europa@bioclean.com

Other Regions

Asia:
malaysia@bioclean.com
Americas:
americas@bioclean.com



BioClean™ is a brand of Nitritex Ltd.
For more information, please visit www.bioclean.com

VFM/1511/PDS12