



## Klebefolienmatte L30-8 CELOS

pure<sup>11</sup>-Nr.: 08041, Hersteller: CELOS

### Zusammenfassung

- Neue pure11-Artikelnummer (ab 01.07.2023): 1108041
- Klebekraft: stark
- Anzahl Lagen: 30
- 30 blaue Lagen pro Matte
- Mattengrundlage: Blau
- Dicke/Stärke der Matte: 1,5 mm
- Besonders hohe Stabilität und Adhäsion
- Robuste Einzellagen durch erhöhte Folienstärke
- Gleichbleibende Klebekraft mit jeder Lage und Produktionscharge
- Antimikrobiell ausgerüstet
- Schichten/Folien mit abnehmender Indexnummerierung

### Empfohlene Reinraumklassen

ISO  3  4  5  6  7  8  9

GMP      C  D

### Produktvarianten

pure<sup>11</sup>-Nr.: 08041B

Farbe: Blau / Maße: 66 x 114 cm / Herst.-Nr.: 08041B / VE: 8 Stück

Quelle: <https://www.pure11.de/klebefolienmatte-l30-8-celos-0>

## Sticky Mat CELOS®

### Product information:

|                    |   |
|--------------------|---|
| <i>Material</i>    | Polyethylen   |
| <i>Application</i> | For particle control and risk reduction in cleanrooms and controlled environments |
| <i>Color</i>       | White or Blue, depending on model   |
| <i>Thickness</i>   | 1.5 mm  |

### Products:

| <i>Part number</i> | <i>Color</i> | <i>Size</i> | <i>Inner packing</i> | <i>Quantity per case</i> |
|--------------------|--------------|-------------|----------------------|--------------------------|
| <b>08040</b>       | White        | 66 x 114 cm | 30 layers/mat        | 8 mats/case              |
| <b>08041</b>       | Blue         | 66 x 114 cm | 30 layers/mat        | 8 mats/case              |

### Characteristics:

- Extreme high stability and adhesion
- Solid single layer due to foil thickness
- Consistent grip strength
- Layers/foils with index numbering
- Antimicrobial
- Easy usage on all surfaces
- Production and packaging in a controlled environment

### Performance parameter:

|                          | <i>Specification</i> | <i>Unit</i> |
|--------------------------|----------------------|-------------|
| Adhesive after aging     | 450 (+/- 30)         | g/mm        |
| Back adhesive strength   | 200 (+/-30)          | g/mm        |
| Bottom adhesive strength | 700 (+/-30)          | g/mm        |
| Heat resistance          | 60                   | °C/48h      |
| Cold resistance          | -1                   | °C/48h      |

pure<sup>11</sup> has made every attempt to ensure the accuracy and reliability of the information provided in this datasheet. However, the information is provided "as is" without warranty of any kind. pure<sup>11</sup> does not accept any responsibility or liability for the accuracy, content, completeness, legality, or reliability of the information contained.