

UltraTape



## Reinraum-Klebeband Vinyl #1160-0,5

pure<sup>11</sup>-Nr. : 1130004 , Marke : UltraTape

### Eigenschaften

- Marke: UltraTape
- Breite in cm: 1 cm
- Beschreibbar
- Länge in m: 32,9
- Chemikalienbeständigkeit
- Klebestärke: mittel
- Klebstoff: Gummi
- LABS frei
- PVC: 100 %
- Reinheitsgrad: Ultrac Clean
- Rückstandsfrei ablösbar

### Material

- 

### Verpackung

- 12STK

### Empfohlene Reinraumklassen

ISO 4 | 5 | 6 | 7 | 8 | 9

GMP C | D

pure<sup>11</sup> GmbH

Bavariafilmplatz 7 | D-82031 Grünwald

Geschäftsführer: Julian Kropp

AG München HRB 171307

T +49 89 5589434 0

F +49 89 5589434 77

www.pure11.de

info@pure11.de

---

## Produktvarianten

---

**pure<sup>11</sup>-Nr.: 1130004BK0\_5I, Reinraum-Klebeband Vinyl #1160-0,5**

Farbe: Schwarz; Breite: 0,5" / VE: 12STK

---

**pure<sup>11</sup>-Nr.: 1130004BL0\_5I, Reinraum-Klebeband Vinyl #1160-0,5**

Farbe: Blau; Breite: 0,5" / VE: 12STK

---

**pure<sup>11</sup>-Nr.: 1130004BN0\_5I, Reinraum-Klebeband Vinyl #1160-0,5**

Farbe: Braun; Breite: 0,5" / VE: 12STK

---

**pure<sup>11</sup>-Nr.: 1130004GY0\_5I, Reinraum-Klebeband Vinyl #1160-0,5**

Farbe: Grau; Breite: 0,5" / VE: 12STK

---

**pure<sup>11</sup>-Nr.: 1130004OR0\_5I, Reinraum-Klebeband Vinyl #1160-0,5**

Farbe: Orange; Breite: 0,5" / VE: 12STK

---

**pure<sup>11</sup>-Nr.: 1130004RD0\_5I, Reinraum-Klebeband Vinyl #1160-0,5**

Farbe: Rot; Breite: 0,5" / VE: 12STK

---

**pure<sup>11</sup>-Nr.: 1130004WH0\_5I, Reinraum-Klebeband Vinyl #1160-0,5**

Farbe: Weiß; Breite: 0,5" / VE: 12STK

---

**pure<sup>11</sup>-Nr.: 1130004YL0\_5I, Reinraum-Klebeband Vinyl #1160-05**

Farbe: Gelb; Breite: 0,5" / VE: 12STK

---

## UT1160 Vinyl Medium Adhesion Cleanroom Tape

### Product Datasheet

#### Description

UltraTape 1160 is a general use vinyl tape. The medium adhesion provides a strong bond and easy release making it perfect for maintenance and construction uses.

- Chemical resistant, durable backing
- Bright durable colors for floor and tool marking
- Low residue
- Easy to write on with a pen

#### Properties

Backing	Vinyl
Adhesive	Rubber
Release Liner	N/A
Backing Thickness	4 mils (0.10mm)
Adhesive Thickness	1 mil (0.02mm)
Adhesion to Stainless Steel	18 oz/in (21 N/100mm)
Operating Temperature	-20°F to 176°F (-28°C to 80°C)
Tensile Strength	13 lb/in (228 N/100 mm)
Length	36 yards
Colors	Black, Blue, Clear, Green, Orange, Red, White, Yellow, Gray Brown, Purple, OSHA Blue

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.





Adhesive Tape & Labels for Critical Environments

---

## Material Safety Data Sheet

**Material Identity:** UT1160 Pressure Sensitive Tape

**Company:**

UltraTape  
9770 Wilsonville Rd. #400  
Wilsonville OR, 97070  
503-427-2880

---

### 1. DOT CLASSIFICATION

Non-hazardous  
Not regulated

---

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient (s)	Cas Number	% (by weight)
Zinc compounds	N982	<0.3
Barium Compounds	N040	<0.1

---

### 3. HAZARDS IDENTIFICATION

**Potential Health Effects:** None known

### 4. STABILITY AND REACTIVITY

**Hazardous Decomposition**

When ignited, will self extinguish, but in on prolonged ignition will generate HCl.

**Hazardous Reaction**

HCl And Other Chlorine compounds may be generated on ignition.

---

### 5. FIRE FIGHTING MEASURES

Will not support combustion, however, CO2 or foam may be used to extinguish an ignition source.

---

### 6. TOXOLOGICAL INFORMATION

Material does not contain substances of concern (Lead, Mercury, Cadmium or Chromium VI).

---

### 7. ECOLOGICAL INFORMATION

Can be recycled.

---

### 8. DISPOSAL CONSIDERATION

**Waste Management Information;**

Dispose of in accordance with all applicable local, state and federal regulations.

---

---

**9. REGULATORY INFORMATION**

Quantities of listed compounds contained in the tapes are not reportable under the article exemption. UltraTape is not a “chemical manufacturer” and the products sold to you are exempt and considered “articles” under SARA Title III (Superfund Amendments and Reauthorization Act of 1986), since they do not release or otherwise result in exposure of a hazardous chemical under normal conditions of use. As a result, no MSDS or Chemical Data Sheets are required.

---

**10. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.

---

End