



## Latex-Handschuhe AccuTech 91-225

pure<sup>11</sup>-Nr.: 05231, Hersteller: Ansell



### Zusammenfassung

- Neue pure11-Artikelnummer (ab 01.07.2023): 1105231
- Material: Latex
- Handspezifisch
- Puderfrei
- AQL-Wert (Acceptable Quality Level): 0.65
- Gammasterilisiert
- Texturiert
- Stärke: 0,25 mm

### Empfohlene Reinraumklassen

ISO	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
GMP	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

### Produktvarianten

**pure<sup>11</sup>-Nr.: 052316**

Farbe: Natur / Größe: 6,0 / Herst.-Nr.: 91-225 / VE: 200 Paar

**pure<sup>11</sup>-Nr.: 052316b**

Farbe: Natur / Größe: 6,5 / Herst.-Nr.: 91-225 / VE: 200 Paar

**pure<sup>11</sup>-Nr.: 052317**

Farbe: Natur / Größe: 7,0 / Herst.-Nr.: 91-225 / VE: 200 Paar

**pure<sup>11</sup>-Nr.: 052317b**

Farbe: Natur / Größe: 7,5 / Herst.-Nr.: 91-225 / VE: 200 Paar

**pure<sup>11</sup>-Nr.: 052318**

Farbe: Natur / Größe: 8,0 / Herst.-Nr.: 91-225 / VE: 200 Paar

---

**pure<sup>11</sup>-Nr.: 052318b**

Farbe: Natur / Größe: 8,5 / Herst.-Nr.: 91-225 / VE: 200 Paar

---

**pure<sup>11</sup>-Nr.: 052319**

Farbe: Natur / Größe: 9,0 / Herst.-Nr.: 91-225 / VE: 200 Paar

Quelle: <https://www.pure11.de/latex-handschuhe-accutech-91-225>

**pure<sup>11</sup> GmbH**

Bavariafilmpfad 7 | D-82031 Grünwald

Geschäftsführer: Gitte Hansen, Julian Kropp

AG München HRB 171307

T +49 89 5589434 0

F +49 89 5589434 77

[www.pure11.de](http://www.pure11.de)

[info@pure11.de](mailto:info@pure11.de)



Natural  
Rubber Latex



Sterile  
Environment

# AccuTech®

## 91-225

### Sterile Natural Rubber Latex Glove

## Setting the standard for comfort and quality

### FEATURES AND BENEFITS:

#### Comfort

The inherent physical properties of natural rubber latex (elasticity, modulus) ensures a very comfortable glove.

#### Dexterity

AccuTech 91-225 gloves are made of a specific formulation of the latex that provides increased flexibility and elasticity. The optimised thickness of the latex, combined with the bisque finish, provides outstanding fingertip sensitivity plus increased handling precision and dexterity. This makes these gloves ideal for intricate handling operations.

#### Allergenicity

Low allergenicity minimizes allergy as protein content is less than 50 µg / gm of polymer.

#### Conformance certified

Lot numbers and expiry dates are displayed on all levels of packaging, from the master bag to the shipping carton. Each lot is supported with a Certificate of Conformance (COC).



### TECHNICAL DATA SHEET:

#### PRODUCT INFORMATION:

<b>Material</b>	Natural Rubber Latex
<b>Color</b>	Natural Color
<b>Glove Design</b>	Hand-specific, Powder Free, Textured Grip
<b>Cuff</b>	Straight Cuff
<b>Sterilization</b>	Cobalt 60, minimum 25kGy Irradiation, Sterility Assurance Level (SAL) 10 <sup>-6</sup>
<b>Clean Room Compatibility</b>	All packaging is printed with cleanroom-compatible IPA-resistant ink. The gloves are triple-bagged for superior contamination control. Recommended for ISO 5 areas.
<b>Audit Standards</b>	ISO 9001, ISO 13485, CE Mark & ISO 11137
<b>Quality Control</b>	AQL - Before packing : GII, AQL 0.65 (Water Leak Test), Final Release: GI AQL 1.0 (Water Leak Test)
<b>Packaging</b>	The glove is packaged one pair per poly wallet, sealed in a poly envelope; 10 pairs per sealed polybag; 5 sealed polybags per master polybag; 4 master polybags per lined carton; 200 pairs per carton. All packaging is printed with cleanroom-compatible IPA-resistant ink. The gloves are triple-bagged for superior contamination control. The polybags have an easy-tear opening.
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	Malaysia

#### PHYSICAL PROPERTIES:

PROPERTY	TYPICAL VALUES							TESTING METHOD
SIZE	6.0	6.5	7.0	7.5	8.0	8.5	9.0	ASTM D3767/EN 420
Length (mm)	300	300	300	300	300	300	300	
Average Palm Width (mm)	80	85	90	95	100	110	115	
Freedom from Holes (Inspection level I)	0.65 AQL							ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm: 0.25) / (mils: 9.8)							ASTM D3767/EN 420
Particle Count	3500 particles/cm <sup>2</sup>							IEST-RP-CC005.2-7
Endotoxin	< 20 EU/pair of gloves							ASTM D7102
	BEFORE AGING			AFTER AGING				
Ultimate Tensile Strength	26 Mpa			23 Mpa				ASTM D 412-06a
Elongation at Break (%)	820			730				ASTM D 412-06a
Modulus @ 500%	3,5			NA				ASTM D 412-06a
Force at break (N)	20			20				EN 455-2

#### ORDERING INFORMATION:

SIZE	6.0	6.5	7.0	7.5	8.0	8.5	9.0
ASPEN	574165	574166	574167	574168	574169	574170	574171



CE 0493

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

North America, Latin America and Caribbean: +1800 800 0444

Asia Pacific: +852 2185 0600

Europe: +32 2 528 74 00

Australia: +61 3 9270 7270

® and ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2013 All Rights Reserved.

