



Nitril-Handschuhe TouchNTuff 92-670

pure¹¹-Nr.: 05331, Hersteller: Ansell

Zusammenfassung

- Neue pure11-Artikelnummer (ab 01.07.2023): 1105331
- Material: Nitril
- Beidhändig tragbar
- Puderfrei
- Latexfrei
- AQL-Wert (Acceptable Quality Level): 1.5
- Texturierte Fingerspitzen
- Einfache Wandstärke 0,10 mm (Mittelfinger)

Empfohlene Reinraumklassen

ISO

3 4 5 6 7 8 9

GMP

D

Produktvarianten

pure¹¹-Nr.: 05331B6c

Farbe: Blau / Größe: 6,5-7,0 / Herst.-Nr.: 92-670 / VE: 1.000 Stück

pure¹¹-Nr.: 05331B7c

Farbe: Blau / Größe: 7,5-8,0 / Herst.-Nr.: 92-670 / VE: 1.000 Stück

pure¹¹-Nr.: 05331B8c

Farbe: Blau / Größe: 8,5-9,0 / Herst.-Nr.: 92-670 / VE: 1.000 Stück

pure¹¹-Nr.: 05331B9c

Farbe: Blau / Größe: 9,5-10,0 / Herst.-Nr.: 92-670 / VE: 1.000 Stück

Quelle: <https://www.pure11.de/nitril-handschuhe-touchntuff-92-670>

NBR

Nitrile



Lab & Utility

TouchNTuff®

92-665 92-670
Nitrile Glove

Textured Single Use Nitrile Gloves

FEATURES AND BENEFITS:

Excellent Puncture Resistance

Three times the puncture resistance of latex or PVC disposables.

Comfort and Chemical Resistant

Made from an innovative nitrile compound which offers outstanding chemical and mechanical properties, comfort and dexterity

100% Nitrile

Contains no waxes, silicone or plasticizers.

Avoid Cuff Roll Down

Rolled cuff. Provides added protection at wrist and ensures a secure fit.

Improved Grip

Textured finish on fingertips.
Improved grip.



Ansell

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

| | 92-665 | 92-670 |
|--------------------------|---|---|
| Material | Nitrile | |
| Color | Light Blue | |
| Glove Design | Ambidextrous, Powder Free, Textured Fingers, Long Cuff | Ambidextrous, Powder Free, Textured Fingers |
| Cuff | Beaded Cuff | |
| Audit Standards | ISO 9001 | |
| Quality Control | EN420, EN374/1,2,3, ASTM D 6319, FDA 21 CFR 177-2600, Arrete 09/11/04, European Regulation 1935/2004, German Recommendation for Food Commodities. | |
| Packaging | 100 gloves per dispensers, 10 dispensers per shipper carton, 1000 gloves per shipper cartons | |
| Storage | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. | |
| Country of Origin | Thailand | |

PHYSICAL PROPERTIES:

| PROPERTY | SIZE | TYPICAL VALUES | | | | TESTING METHOD |
|-------------------------|--------|----------------|-----------|-----------|-------------|-------------------|
| | | S 6½-7 | M 7½-8 | L 8½-9 | XL 9½-10 | |
| Length (mm) | 92-665 | 300 | 300 | 300 | 300 | ASTM D3767/EN 420 |
| | 92-670 | 240 | 240 | 240 | 240 | |
| Average Palm Width (mm) | | 85 | 96 | 105 | 111 | |

| | | |
|---|--------------------------|---------------------|
| Freedom from Holes (Inspection level I) | 1.5 AQL | ASTM D5151/EN 374-2 |
| Palm Thickness Single Wall | (mm: 0.11) / (mils: 4.3) | ASTM D3767/EN 420 |

| | BEFORE AGING | AFTER AGING | |
|---------------------------|--------------|-------------|----------------|
| Ultimate Tensile Strength | > 14 Mpa | > 14 Mpa | ASTM D 412-06a |
| Elongation at Break (%) | > 500 | > 400 | ASTM D 412-06a |
| Force at break (N) | > 6 | > 6 | EN 455-2 |

ORDERING INFORMATION:

| | SIZE | S 6½-7 | M 7½-8 | L 8½-9 | XL 9½-10 |
|--------|------|-----------|-----------|-----------|-------------|
| 92-665 | ASPN | 588782 | 588783 | 588784 | 588785 |
| 92-670 | ASPN | 588170 | 588171 | 588172 | 588173 |



For additional information visit us at www.ansell.com, or call us at
 North America, Latin America and Caribbean: +1800 800 0444
 Asia Pacific: +852 2185 0600
 Europe: +32 2 528 74 00
 Australia: +61 3 9270 7270

® and ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2013 All Rights Reserved.